KANEPACKAGE PHILIPPINE INC. PRI				SSITE INSPI (OFFSET I		RT	Control No.		
Inspector's Name					Customer		I .		
Printing Date					Item Code				
External Provider					Item Descrip	ption			
Machine Name					Traceability	Code		Quantity	
A. Reference Materials						Rem	arks		
Approved LSD reference	☐ Available	□ U	navailable						
Digital proof	☐ Available☐ Unavailable								
Diecut film	Available Unavailable								
Defect Limit Criteria	Available Unavailable								
KPPI drawing reference	Available	□ U	navailable						
Pokayoke - Panel A Good No Good				Background:					
Pokayoke - Panel B	B Good No Good			Text:					
Bleeding Size(mm)	☐ Good ☐ No Good			Right: Left: Bottom:					
B. Material & Machine Condition						Rem	arks		
Claycoat brand / Paper shade									
Claycoat sheet size (Drawing vs Actual)									
Claycoat grammage/ caliper (Drawing vs Actual)									
Claycoat grain direction									
Spray powder (brand & % distribution)									
Varnish (WB or UV, viscosity, expiration,									
Dampening water tempera	ture (°C)								
Color Sequence (Unit)				Ink Density					
1st	3rd			5th			Panel A	Panel B	
2nd 4th				6th		Cyan (C)			
Gloss Value					Process Color	Magenta (M)			
1st 3rd			5th	1 100033 00101	Yellow (Y)				
2nd 4th				6th		Black (K)			
	b Test Result	(Afte	r 24hrs Cu	ring)	Special Color	1			
Background (Yellow / Blue) (Gray)			SON Logo	Note: Distance of slide: 122mm	Special Color 2				
☐ Good ☐ Good	☐ Good		Good	Rate of reciprocating: 40±2 times/ minute	Remarks				
☐ No Good ☐ No Good	□ No God		No Good	Max. no. of strokes: 600					
□ N/A □ N/A	□ N/A		N/A	Load apply: 500±5 grams					
C. Checking of Printed Output				Remarks					
Text and characters Good No Good									
Visual apperance ☐ Good ☐ No Good									
Barcode reading Good No Good									
D. Problems Encountered									
E. Recorded Downtime							Overall Judgement		
							PASSED		
							☐ PASSED ☐ FAILED		
Pre	pared			Che	ecked		FAILED	Approved	